

CT106

WIRELESS TRANSMITTER

Instant Audio/Visual Alerts

Magnetic Sensor, User-Programmable Alerts, Fully Supervised

The CT-106 Wireless Magnetic Sensor is designed to monitor locations such as doors and windows. When the paired magnet separates from the CT-106, a pre-programmed alphanumeric message to wireless paging receivers such as pocket pagers, alphanumeric LED message boards and paging base stations. In addition, the CT-106 can send activation command to wireless PA speakers for pre-programmed message playback, remotely initiate a two-way intercom communication and activate wireless corridor dome lights.

The CT-106 can be programmed into "System Mode" where all its transmissions are being received and processed by a paging base station. In this configuration, the paging station unit can initiate an automated sequence of paging events according to a pre-defined script for every CT-106 activity.



CT106 KEY FEATURES



ELEVATED ALERTS

Alert Supervisor pager when call is not cleared within pre-defined period of time



ALERT REPEAT

Repeat alert up to 9 times when call is not cleared in pre-defined period of time



DELAYED ACTIVATION

Delay the call transmission for a pre-defined time, then send alert if call isn't cleared



MULTIPLE ACTIVATIONS

Activates wireless strobe lights, PA speakers, pagers and LED message boards



FULLY SUPERVISED

Sends periodical status transmissions according to pre-defined intervals



LOW BATTERY ALERT

Automatically send a message to report low battery status



VISIPILEX

1287 BARCLAY BLVD


BUFFALO GROVE, IL 60089

PHONE: 877-918-7243

FAX: 847-229-0259

EMAIL: INFO@VISIPILEX.COM

WEB: WWW.VISIPILEX.COM



CT106 SPECIFICATIONS

Parameter	Description
Color	Off-white body
Frequency Band	UHF 402-470 MHz
Range	300'
Dimensions	1.8" x 2.4" x 0.8", 46mm x 61mm x 20mm (W x H x D)
Weight	1.6oz, 45g
Power	Single CR2 3V Lithium battery
Operating Conditions	Temperature 32°-140°, Humidity 0-90% non-condensing
RF Power	10 mW
Programming	PC Based programming
Call Cancel	Internal Magnetic Switch
Signalling Time	2-4 Seconds
Stability	Better than 5 PPM
Paging Format	POCSAG, 512, 1200 or 2400 BPS
Channel Spacing	12.5 KHz - Narrow Band
Activation Codes	Calls, Cancel & Low Battery
Options	WPA-1013 (Wall Bracket), WPA-1021 (Lithium Battery), WPA-1025 (Programming Cable)
Warranty	One Year Limited Warranty



VISIPLEX

1287 BARCLAY BLVD
BUFFALO GROVE, IL 60089

PHONE: 877-918-7243

FAX: 847-229-0259

EMAIL: INFO@VISIPLEX.COM

WEB: WWW.VISIPLEX.COM